

Compatible Material	Protective Coating, Solvents
Control Type	Fixed Ratio
Features	NXT Air Motor, DataTrak Control, Modular Air Valve, Quick Disconnect, Graco Xtreme Pump Lower with Built-In Filter
Fluid Inlet Thread Gender	Male
Fluid Inlet Thread Type	NPT
Fluid Outlet Size (cm)	2.54
Fluid Outlet Size (mm)	25.4
Fluid Outlet Thread Gender	Female
Frame Configuration	Heavy-Duty Cart
Hose Inlet Diameter (cm)	1.905
Hose Inlet Diameter (mm)	19.05
Includes	XL10000 High Performance Motor, Heavy Duty Cart, XHF Spray Gun, Hose

Inlet Paint Strainer	8 Mesh, 16 Mesh
Material Application	Paints, Primers
Maximum Sound Pressure Level (dB(A))	83
Maximum Working Pressure (MPa)	50
Maximum Working Pressure (bar)	500
Maximum Working Pressure (kPa)	50000
Model	King
Motor Type	Pneumatic Motor, De-Icing
Number of Guns	1
Outlet Paint Filter	60 Mesh
Power Source	Air
Pressure Control Type	Air Regulator
Product Type	Single Leg

Pump Rod Type	Chromex
Pump Sleeve Material	Hard Chrome, Stainless Steel
Pump Type	2-Ball Positive Displacement
Series	XL70
Standards Met	CE, Ex
Type	Airless Sprayer
Wetted Material	Carbon Steel, Alloy Steel, Stainless Steel